

SD 322-31 dry and storage cabinet

The SD Series is equipped with one reliable dry unit to constantly maintain low humidity of < 5% RH. Easy to operate, this comprehensive range is recommended for the purpose storage of SMDs at low humidity. Engineered for medium to long-term constant low humidity storage, the SD-322 - 31 is ideal for the moisture-proof and anti-oxidation storage of wide-ranging technologies and conform with IPC Standard 33b.

Scope of delivery

The cabinet will delivered including 3 shelves, 2 keys for the door and adjustable legs.

Dry Unit

One U-3000 dry unit ensure a fast and interruption free dehumidification to a low level of less than <5 %RH. The dry units work very silent and maintenance-free.

Control System

A digital panel shows the present humidity level and temperature in the cabinet. All settings can be justified at the touch of a button.

ESD

ESD-safe cabinet according to EN 61340-5-1:2001, including window and dry unit



Dry Performance

The dry unit dehumidifies the air in the cabinet to a minimum of 3 %RH.

Dehumidification

The recovery time of the cabinet after a 10 sec Open door-time is 60 minutes to <3%RH.



Technical Data

External Dimension	99 x 45 x 101 cm
Internal Dimension	90 x 42 x 85 cm
Weight	68 kg
Volume	320 l
Dry Unit	U-3000 for < 0.5 % RH
Control	Digital
Voltage	Variations are available
Average power consumption	20 W

