

120mm

30

30

202.5mm

90mm

100mm

15

80mm

202.5mm

15

660mm

675mm

Caution
This Bag contains
MOISTURE-SENSITIVE DEVICES

LEVEL
 if blank, see adjacent bar code label

1. Calculated shelf life in sealed bag: 12 months at < 40 °C and < 90 % relative humidity (RH)
2. Peak package body temperature : _____ °C
if blank, see adjacent bar code label
3. After bag is opened, devices that will be subjected to reflow solder or other high temperature process must
a) Mounted within: _____ hours of factory conditions
if blank, see adjacent bar code label
< 30 °C/60 % RH, OR
b) Stored at < 10 % RH
4. Devices require bake, before mounting, if:
a) Humidity Indicator Card is > 10 % when read at 23±5 °C
b) 3a or 3b not met.
5. If baking is required, devices may be baked for 48 hours at 125±5 °C
Note: If device containers cannot be subjected to high temperature or shorter bake times are desired, reference IPC/JEDEC J-STD-033 for bake procedure

Bag Seal Date: _____
if blank, see adjacent bar code label

Note: Level and body temperature defined by IPC/JEDEC J-STD-020

SUPER DRY®
STATIC SHIELD
MOISTURE BARRIER BAG

CAUTION
ESD and Moisture Sensitive
Electronic Devices Enclosed

DO NOT OPEN
EXCEPT UNDER
CONTROLLED
CONDITIONS

www.superdry.info
MIL-B 81705-REV-C

Ref No:SDB 1066

Lot no:

10

100mm

10