

270mm

30
30

122.5mm

100mm

15

80mm

122.5mm

15

515mm

90mm

Caution
This Bag contains
MOISTURE-SENSITIVE DEVICES

LEVEL
If blank, see adjacent bar code label

1. Calculated shelf life in sealed bag: 12 months at < 40 °C and < 90 % relative humidity (RH)
2. Peak package body temperature: _____ °C
If blank, see adjacent bar code label
3. After bag is opened, devices that will be subjected to reflow solder or other high temperature process must
 - a) Mounted within: _____ hours of factory conditions
If blank, see adjacent bar code label
 - b) Stored at < 10 % RH
4. Devices require bake, before mounting, if:
 - a) Humidity Indicator Card is > 10 % when read at 23 ± 5 °C
 - b) 3a or 3b not met.
5. If baking is required, devices may be baked for 48 hours at 125 ± 5 °C

Note: If device containers cannot be subjected to high temperature or shorter bake times are desired, reference IPC/JEDEC J-STD-033 for bake procedure

Bag Seal Date: _____
If blank, see adjacent bar code label

Note: Level and body temperature defined by IPC/JEDEC J-STD-020

SUPER DRY®
STATIC SHIELD
MOISTURE BARRIER BAG

CAUTION
ESD and Moisture Sensitive
Electronic Devices Enclosed

DO NOT OPEN
EXCEPT UNDER
CONTROLLED
CONDITIONS

www.superdry.info
MIL-B 81705-REV-C

Ref No:SDB 2550

Lot no:

500mm

250mm

10

10